

SEPARATOR FOR BATTERY AND MANUFACTURE THEREOF

Publication number: JP1248462
Publication date: 1989-10-04
Inventor: IWAKI TSUTOMU; MORIWAKI YOSHIO; SHINTANI
AKIYOSHI
Applicant: MATSUSHITA ELECTRIC IND CO LTD
Classification:
- **international:** **H01M2/16; H01M2/16; (IPC1-7): H01M2/16**
- **european:** H01M2/16B3
Application number: JP19880076714 19880330
Priority number(s): JP19880076714 19880330

Report a data error here

Abstract of JP1248462

PURPOSE: To improve gas absorbency in charging and to lengthen life by using a separator made of a sulfuric acid treated porous body comprising polyvinyl alcohol fibers and polyolefin fibers.

CONSTITUTION: A sulfuric acid treated porous body comprising polyvinyl alcohol fibers and polyolefin fibers is used as a separator. A sulfuric acid solution is added to the porous body comprising polyvinyl alcohol fibers and polyolefin fibers and they are heated to introduce a sulfone group into a polyvinyl alcohol group. This porous body has no abnormal hydrophilic nature and retains proper hydrophilic nature for a long time. The difficulty of transfer of oxygen gas from a positive electrode to a negative electrode in charging is removed and the life of a battery is lengthened.

Data supplied from the **esp@cenet** database - Worldwide